#### **BELLEVUE FLFV 1555**

# **AVFAX CODE 6105**

UTC +8 YBI U CERT



WA 273646S 1203538E VAR 1 DEG E AD OPR IGO Limited, PO Box 496, South Perth, WA, 6951, Email: craig.gaffnev@igo.com.au, PH AD Manager 0407 505 397.

#### **REMARKS**

Restricted OPS - PPR from AD OPR.

## HANDLING SERVICES AND FACILITIES

Terminal facilities. No fuel available. Contact ARO.

# **APRONS AND TAXIWAYS**

TWY A - Code C. 15M sealed.

## **AERODROME OBSTACLES**

- Terrain 1,832FT AMSL BRG 332 DEG MAG APRX 2.8NM FM ARP, penetrates OBST 1 limitation SFC by 82FT.
- Tower 1,795FT AMSL BRG 297 DEG MAG APRX 1.6NM FM ARP. 2.
- 3.
  - а 1,767FT AMSL BTN BRG 330-340 DEG MAG APRX 1.3NM FM ARP (temporary). Infringes HZS up to 50FT.
  - 1,763FT AMSL BRG 315 DEG MAG 1.24NM FM ARP. Head frame infringes inner HZS by up to 110FT.

#### PHYSICAL CHARACTERISTICS

006 66a PCN 32 /F /C /1000 (145PSI) /T Sealed. 01/19 **WID 30 RWS 150** 

AERODROME AND APPROACH LIGHTING

RWY 01/19 LIRL(3) SDRY PWR AVRI

BY PRIOR ARRANGEMENT

3.0 DEG49FT SDBY PWR AVBL RWY 01/19 PAPI(1)

BY PRIOR ARRANGEMENT

BY PRIOR ARRANGEMENT RWY 01/19 PTBL(2)

- (1) Left side only. Manual activation with 30MIN PN.
- (2)EMERG only. 60MIN PN. CTC ARO.
- (3)30MIN PN.

#### OTHER LIGHTING

- SDBY PWR switchover time: 15 MIN. 1.
- TWY LGT: Blue edge. 2.

## ATS AND AERODROME COMMUNICATION FACILITIES

FIA MELBOURNE CENTRE 118.95 Circuit area

# LOCAL TRAFFIC REGULATIONS

- 1 All ACFT to use turn pads, MAX turn radius at MNM speed.
- All ACFT ABV 5,700KG MTOW must park on marked bays using appropriate lead-in lines.

#### FLIGHT PROCEDURES

Right hand circuit on RWY 01 due to terrain to the NW of the AD.

#### **CTAF** 126.5

AFRU at Leinster. Signal not AVBL on ground Bellevue.

## ADDITIONAL INFORMATION

Bird hazard exists (budgies, swallows, parrots and crows) in VCY of AD.

#### CHARTS RELATED TO THE AERODROME

- WAC 3345. 1.
- 2. Also refer to AIP Departure and Approach Procedures.

