

CAROSUE DAM**ELEV 1291****AVFAX CODE 6117**

WA

UTC +8

YSCD


301025S

1221920E

VAR 1 DEG E

CERT

AD OPR Northern Star (Carosue Dam) Pty Ltd, Level 1, 388 Hay Street, Subiaco, WA, 6008. Email: aerodromecarosuedam@nsrtd.com. PH 08 6188 2100. ARO 08 6229 9014. ARO AH 0477 516 011.

**REMARKS**

1. PPR from AD OPR.
2. Parking by prior arrangement with AD OPR.

HANDLING SERVICES AND FACILITIES

Nil fuel AVBL.

PASSENGER FACILITIES

Passenger terminal/WC.

PHYSICAL CHARACTERISTICS

06/24 061 66a PCN 27 /F /B /1076 (156PSI) /T Sealed WID 30 RWS 150

AERODROME AND APPROACH LIGHTING

RWY 06/24	PAPI(2)	3.0 DEG48.5FT	BY PRIOR
RWY 06/24	PTBL(1)		ARRANGEMENT
			BY PRIOR
			ARRANGEMENT

- (1) EMERG lighting AVBL with 120 MIN PN to ARO.
- (2) Left side only. Manual activation of PAPI AVBL with 30MIN PN. HJ only.

OTHER LIGHTING

1. RWY edge light spacing: 06/24: 87M (PTBL).
2. No mains PWR AVBL - PAPI PWR supplied by generators.

ATS AND AERODROME COMMUNICATION FACILITIES

FIA	MELBOURNE CENTRE	125.75
UNICOM	CAROSUE DAM UNICOM	126.7

LOCAL TRAFFIC REGULATIONS

1. All ACFT to follow APN markings.
2. All fixed wing ACFT must make MAX RAD turns at MNM speed at all RWY ends to avoid SFC damage.
3. All fixed wing ACFT to use idle power for movements on the APN with the exception of breakaway thrust to initiate taxi. ACFT that cannot comply with this restriction must advise the AD OPR prior to departure.
4. Day OPS only EXC for EMERG.

CTAF - AFRU 126.7**CHARTS RELATED TO THE AERODROME**

1. WAC 3352.
2. Also refer to AIP Departure and Approach Procedures.