

MELBOURNE/ESSENDON

RWY	(CN)	TORA	TODA	ASDA	LDA
08	(4)	1921 (6302)	1981 (6499) (2.59%)	1921 (6302)	1921 (6302)
26	(4)	1921 (6302)	1981 (6499) (3.73%)	1921 (6302)	1921 (6302)

1. OBST in flyover area of RWS refer ERSA.

2. Multiple lit and unlit masts BTN 2061-2204M FM RWY 26 SOT BTN 101M L and 101M R RCL.

3. Masts infringe 2% TKOF SFC up to 3.3% not ABV 261FT AMSL.

4. Masts are street lights along the Tullamarine Freeway.

Slope 0.4% down to the W for 700M then 0.2% down to E for the remainder. RWY WID 45 RWS WID 180 Graded 150

17	(3)	1503 (4931)	1563 (5128) (3.04%)	1503 (4931)	1503 (4931)
35	(3)	1503 (4931)	1563 (5128) (1.82%)	1503 (4931)	1503 (4931)

RWY 35 fixed distance and touch down zone markings displaced 33M to N.

Slope 0.9% down to S. RWY WID 45 RWS WID 150

SUPPLEMENTARY TAKEOFF DISTANCES

RWY08- 1918(6293)(1.6) 1949(6394)(1.9) 1968(6457)(2.2) 1976(6483)(2.5)

RWY26- 1713(5620)(1.6) 1781(5843)(1.9) 1831(6007)(2.2) 1871(6138)(2.5) 1951(6401)(3.3)

RWY17- 1427(4682)(1.6) 1470(4823)(1.9) 1501(4924)(2.2) 1528(5013)(2.5)

RWY35- 1302(4272)(1.6)