


**MOUNT MAGNET****ELEV 1354****AVFAX CODE 6011**

WA  
280658S 1175030E UTC +8 YMOG  
VAR 0 DEG E CERT  
AD OPR Shire of Mount Magnet, PO Box 62, Mt Magnet, WA, 6638. Email:  
works@mtmagnet.wa.gov.au. PH 08 9963 3000 BH. ARO AH 0427 634 241 or  
0409 058 809. Fax 08 9963 4133.

**REMARKS**

- AD charges apply. Contact AD Operator.
- This AD is a Security Controlled Airport.

**AERODROME OBSTACLES**

- Fence 989M FM SOT RWY 04, 5FT AGL.
- Primary IWI 1,362FT AMSL BRG 017 DEG MAG 100M FM ARP.  
Infringes transitional SFC by 2FT.

**METEOROLOGICAL INFORMATION PROVIDED**

- TAF CAT D, METAR/SPECI.
- AWIS PH 08 6216 2627 - report faults to BoM.
- AWIS FREQ 122.975 (requires one-second pulse to activate) - Report faults to AD OPR.

**PHYSICAL CHARACTERISTICS**

04/22	035	30c	5700/735 (107PSI) Unrated. Red silt sand	WID 30	RWS 90
16/34	157	59a	PCN 9 /F /A /850 (123PSI) /U	WID 30	RWS 90

**AERODROME AND APPROACH LIGHTING**

RWY 16/34 LIRL AFRU+PAL 126.7 SDBY PWR AVBL

- RWY edge light spacing: 16/34: 60M.
- Secondary power supply requires 10 SEC switchover time for automatic generator to fully activate.

**OTHER LIGHTING**

TWY LGT: Blue edge.

**ATS AND AERODROME COMMUNICATION FACILITIES**

FIA MELBOURNE CENTRE 124.8 Circuit Area

**RADIO NAVIGATION AND LANDING AIDS**

NDB MOG 395 280350.8S 1175037.4E Range 85 (HN 85) (1)  
(1) Pilot monitored - 183/3.4 to ARP.

**LOCAL TRAFFIC REGULATIONS**

- ACFT ABV 5,700KG are required to use RWY 16/34 only and to taxi on RCL and turn at turning nodes. All turns to be MNM speed, MAX RAD.
- Due to limited apron space H24 PN required for all non RPT ACFT above 5,700KG.
- Light ACFT PRKG Bay at S side of APN. Tie-down (not rated) provided.

**CTAF - AFRU 126.7**

**ADDITIONAL INFORMATION**

Inspections are carried out on MON, WED, THU and FRI. Additional inspections are AVBL and with 60 MIN PN.

**CHARTS RELATED TO THE AERODROME**

- WAC 3351.
- Also refer to AIP Departure and Approach Procedures.