

TINDAL

RWY	(CN)	TORA	TODA	ASDA	LDA
14	(MIL)	2444 (8018)	2589 (8494) (3.3%)	2444 (8018)	2444 (8018)
32	(MIL)	2444 (8018)	2504 (8215) (1.6%)	2444 (8018)	2444 (8018)

1. TKOF/Climb SFC inner edge WID 180.

Slope Level to SE to 317M, then up 0.3% to 1515M, then up 0.1% to RWY end. RWY WID 45
RWS WID 280

OPERATIONAL READINESS PLATFORMS (ORP)

TEMPO DISP THR RWY 14 marked by four white cones either side of the RWY, 242M from the RWY 14 end.

RWY	TORA	TODA	ASDA	LDA
14	2444(8018)	2589(8494)(3.3%)	2444(8018)	2202(7224)
32	2444(8018)	2504(8215)(3.8)	2444(8018)	2444(8018)

SUPPLEMENTARY TAKEOFF DISTANCES

RWY				
32	2237(7339)(1.6)	2293(7522)(1.9)	2308(7572)(2.0)	2333(7654)(2.2)
	2364(7755)(2.5)	2402(7880)(3.0)	2419(7936)(3.3)	

TEMPO DISP THR RWY 32 marked by four white cones either side of the RWY, 617M from the RWY 32 end.

RWY	TORA	TODA	ASDA	LDA
14	1827(5994)	1827(5994)(5.0%)	1827(5994)	1827(5994)
32	1827(5994)	1887(6190)(1.6%)	1827(5994)	1827(5994)

SUPPLEMENTARY TAKEOFF DISTANCES

RWY				
14	1639(5377)(1.6%)	1729(5672)(2.5%)	1769(5803)(3.3%)	

SUPPLEMENTARY TAKEOFF DISTANCES

RWY14- 2239(7346)(1.6) 2348(7703)(1.9) 2362(7749)(2.0) 2406(7894)(2.2) 2444(8018)(2.5)