

TAREE

RWY	(CN)	TORA	TODA	ASDA	LDA
04	(3)	1504 (4934)	1564 (5131) (2.48%)	1504 (4934)	1389 (4557)
		RESA dimensions 60M X 60M commences from RWY end. RWY 04 DTHR 115M (377FT).			
22	(3)	1504 (4934)	1564 (5131) (21.99%)	1504 (4934)	1504 (4934)
		RESA dimensions 60M X 60M commences from RWY end. RWY 04/22: TKOF climb SFC inner edge 150M. CAUTION: NE end unlit OBST fence 3FT ABV and 89M E of RWY CL has not been taken into account in calculation of TODA GRAD and STODA. Slope 0.5% down to NE. RWY WID 30 RWS WID 150 Graded 90			
12	(1)	564 (1850)	624 (2047) (3.75%)	564 (1850)	564 (1850)
30	(1)	564 (1850)	624 (2047) (5%)	564 (1850)	564 (1850)
		1. Trees infringe transitional SFC on S side of the RWY. 2. RWY 12/30 RWS S side transitional surface infringed. Slope 0.2% down to SE. RWY WID 18 RWS WID 60			

SUPPLEMENTARY TAKEOFF DISTANCES

RWY04- 1334(4377)(1.6) 1487(4879)(1.9) 1560(5118)(2.2)
 RWY22- 1042(3419)(1.9) 1221(4006)(2.2) 1344(4409)(2.5) 1482(4862)(3.3) 1518(4980)(5.0)