

ADELAIDE/PARAFIELD

RWY	(CN)	TORA	TODA	ASDA	LDA
03L	(2)	1350 (4429)	1410 (4626) (2.8%)	1350 (4429)	1350 (4429)
RESA dimensions 60M X 60M commences from RWS end. Landing RWY 03L: Unlit OBST 7.9FT ABV and 215M S RWS end. Top of fence marked by red and white 0.6M square hazard signs.					
21R	(2)	1350 (4429)	1410 (4626) (1.94%)	1350 (4429)	1350 (4429)
RESA dimensions 60M X 60M commences from RWS end. TKOF RWY 21R: Unlit OBST 6.7FT ABV CWY and 215M S RWS end is not taken into account in the calculation of TODA GRAD and STODA. Top of fence marked by red and white 0.6M square hazard signs. Slope 0.4% down to SW. RWY WID 18 RWS WID 90 Graded 90					
03R	(2)	1279 (4196)	1339 (4393) (3.58%)	1279 (4196)	1279 (4196)
Landing RWY 03R: OBST fence 7.9FT ABV and 141M S RWS end. Top of fence marked by red and white 0.6M square hazard signs.					
21L	(2)	1279 (4196)	1339 (4393) (1.56%)	1279 (4196)	1279 (4196)
TKOF RWY 21L: OBST fence 7FT ABV CWY and 141M S RWS end not taken into account in the calculation of STODA GRAD. Top of fence marked by red and white 0.6M square hazard signs. Slope 0.5% down to SW. RWY WID 18 RWS WID 90 Graded 90					
08L	(2)	958 (3143)	1018 (3340) (2.98%)	958 (3143)	958 (3143)
26R	(2)	958 (3143)	1018 (3340) (3.88%)	958 (3143)	958 (3143)
Slope 0.5% down to SW. RWY WID 18 RWS WID 90 Graded 90					
08R	(2)	992 (3255)	1052 (3451) (2.78%)	992 (3255)	992 (3255)
26L	(2)	992 (3255)	1052 (3451) (3.8%)	992 (3255)	992 (3255)
Slope 0.1% down to W. RWY WID 18 RWS WID 90 Graded 90					

SUPPLEMENTARY TAKEOFF DISTANCES

RWY03L-	914(2999)(1.9)	1158(3799)(2.2)	1334(4377)(2.5)
RWY21R-	1154(3786)(1.6)	1402(4600)(1.9)	
RWY03R-	872(2861)(2.2)	1046(3432)(2.5)	1287(4222)(3.3)
RWY26R-	944(3097)(3.3)		
RWY08R-	904(2966)(2.5)		
RWY26L-	853(2799)(2.5)	990(3248)(3.3)	

TAXIWAY INTERSECTION DECLARED DISTANCES

RWY03L- TKOF from TWY B1; RWY remaining 1158(3799) reduce all DIST by 192(630)