

BENDIGO

RWY	(CN)	TORA	TODA	ASDA	LDA
05	(1)	767 (2516)	827 (2713) (4.98%)	767 (2516)	767 (2516)
RESA dimensions 60M X 36M commences from RWS end.					
23	(1)	767 (2516)	827 (2713) (5.06%)	767 (2516)	767 (2516)
RESA dimensions 60M X 36M commences from RWS end.					
Slope 0.4% down to NE. RWY WID 18 RWS WID 60 Graded 60					
17	(3)	1600 (5249)	1660 (5446) (3.25%)	1600 (5249)	1600 (5249)
RESA dimensions 90M X 60M commences from RWS end.					
1. Unlit OBST fence 15.3FT ABV and 82M S of RWS end has not been taken into account in the calculation of the TODA GRAD and STODA.					
2. Transient OBST (vehicle) 32FT AGL and 1870M FM SOT RWY 17 has not been taken into account in the calculation of TODA GRAD and STODA.					
35	(3)	1600 (5249)	1660 (5446) (2.92%)	1600 (5249)	1600 (5249)
RESA dimensions 90M X 60M commences from RWS end.					
Slope 600M N end 0.9% down to S, 1000M S end 1.1% down to N. RWY WID 30 RWS WID 150 Graded 90					

SUPPLEMENTARY TAKEOFF DISTANCES

RWY23-	822(2697)(5.0)				
RWY17-	805(2641)(2.2)	1133(3717)(2.5)			
RWY35-	971(3186)(1.6)	1188(3898)(1.9)	1414(4639)(2.2)	1549(5082)(2.5)	