

CARNARVON

RWY	(CN)	TORA	TODA	ASDA	LDA
04	(3)	1619 (5312)	1679 (5508) (2.12%)	1619 (5312)	1619 (5312)
RESA dimensions 90M X 90M commences from RWS end.					
RWY 04 has non-standard approach surface - inner edge of APCH SFC 40M from RWY end.					
22	(3)	1619 (5312)	1679 (5508) (3.83%)	1619 (5312)	1619 (5312)
RESA dimensions 90M X 90M commences from RWS end.					
RWY 04/22 APCH inner edge length 150M.					
Slope 0.1% down to SW. RWY WID 30 RWS WID 150					
18	(2)	1140 (3740)	1200 (3937) (2.29%)	1140 (3740)	1140 (3740)
36	(2)	1140 (3740)	1200 (3937) (3.99%)	1140 (3740)	1140 (3740)
TKOF GRAD 4.7%.					
Slope 0.1% down to S. RWY WID 30 RWS WID 90					

SUPPLEMENTARY TAKEOFF DISTANCES

RWY04-	1353(4439)(1.6)	1563(5128)(1.9)			
RWY22-	1182(3878)(1.6)	1313(4308)(1.9)	1410(4626)(2.2)	1485(4872)(2.5)	1619(5312)(3.3)
RWY18-	1083(3553)(1.6)	1184(3884)(1.9)	1197(3927)(2.2)		
RWY36-	904(2966)(1.9)	1005(3297)(2.2)	1081(3547)(2.5)	1188(3898)(3.3)	