

**MOUNT HOTHAM****ELEV 4260****AVFAX CODE 3065**

VIC

UTC +10

YHOT


370254S

1472003E

VAR 13 DEG E

CERT

AD OPR Mt Hotham Airport Operations Pty Ltd, PO Box 8280, Northland Centre, VIC, 3072.

ARO 0467 072 476 (H24). Fax AD OPS 03 5159 6776. Website: [www.mthothamairport.com.au](http://www.mthothamairport.com.au).**REMARKS**

- AD Charges: All ACFT.
- PPR FM AD OPR for all night and non-RPT OPS, refer to website for OPR approval (PDF).
- Call-out fee applies for approved night OPS.

**HANDLING SERVICES AND FACILITIES**

JET A1 year round, 2200-0600 UTC DLY; JUN-SEP - 4HR PN. OT 24HR PN. CTC AD OPR.

Call-out fee applies weekends and PH during non-winter period. EFTPOS and credit cards only.

**PASSENGER FACILITIES**

June/September - PT/HC/BU/AC/LG/RF/WC. OT restricted hours.

**APRONS AND TAXIWAYS**

- TWY B not AVBL to ACFT ABV 5,700KG MTOW.
- TWY B AVBL to ACFT with a wingspan up to and not exceeding 15M.

**AERODROME OBSTACLES**

- Lit mast 4,460FT, BRG 291 DEG MAG 2,873M FM RWY 29 THR, 0.4M L of RCL.
- Trees:
  - 4,517FT AMSL PSN 370204.70S 1471848.02E. Infringes APCH SFC by 76FT.
  - 4,446FT AMSL PSN 370221.17S 1471856.06E. Infringes APCH SFC by 54FT.
  - 4,409FT AMSL PSN 370228.12S 1471904.67E. Infringes TKOF SFC by 89FT.
  - 4,413FT AMSL PSN 370226.12S 1471902.76E. Infringes TKOF SFC by 88FT.
  - 4,454FT AMSL PSN 370226.11S 1471854.18E. Infringes TNS by 8FT.
  - 4,412FT AMSL PSN 370228.42S 1471904.02E. Infringes TNS by 16FT.
  - 4,389FT AMSL PSN 370244.4S 1472013.2E. Infringes TNS by 4FT.

**METEOROLOGICAL INFORMATION PROVIDED**

- METAR/SPECI.
- AWIS Phone 03 8470 3217 - Report faults to BoM.
- AWIS FREQ 128.05 (one-second transmit pulse to activate) - Report faults to AD OPR.

**PHYSICAL CHARACTERISTICS**

11/29 111 48a PCR 175/F/C/1.14 MPa/T

WID 30 RWS 90

**AERODROME AND APPROACH LIGHTING**

|           |         |             |                                          |
|-----------|---------|-------------|------------------------------------------|
| RWY 11/29 | LIRL(2) |             | SDBY PWR AVBL BY<br>PRIOR<br>ARRANGEMENT |
| RWY 11    | PAPI(1) | 3.9 DEG42FT | SDBY PWR AVBL BY<br>PRIOR<br>ARRANGEMENT |
| RWY 29    | PAPI(1) | 3.0 DEG41FT | SDBY PWR AVBL BY<br>PRIOR<br>ARRANGEMENT |

- (1) Left side. PN REQ
- (2) PN REQ
1. RWY edge light spacing: 11/29: 56M.
2. From JUN to SEP the primary WDI located S RWY 11/29 will be yellow.
3. Main PWR supply serviced by AD generator.

**OTHER LIGHTING**

1. Secondary PWR switchover time: 15 SEC.
2. TWY LGT: Blue edge on TWY A only.

**ATS AND AERODROME COMMUNICATION FACILITIES**

FIA MELBOURNE CENTRE 125.2 6500FT

**LOCAL TRAFFIC REGULATIONS**

All ACFT required to execute 180DEG turns at RWY end turning nodes only.

**FLIGHT PROCEDURES**

1. Right hand circuits required when OPR on RWY 29.
2. Pilots are requested to avoid overflying the Alpine National Park (Bogong Unit).

**CTAF - AFRU** 126.75

**CHARTS RELATED TO THE AERODROME**

1. WAC 3470.
  2. Also refer to AIP Departure and Approach Procedures.
-