


STAWELL**ELEV 807****AVFAX CODE 3041**

VIC
370418S 1424425E UTC +10 YSWL
VAR 11 DEG E CERT
AD OPR Northern Grampians Shire Council, Town Hall, Stawell, VIC, 3380.
ARO 03 5358 8700 H24.

HANDLING SERVICES AND FACILITIES

Aero Refuellers: JET A1 and AVGAS H24 self-serve bowsers. Accepts Aero Refuellers cards, V and MC. PH 02 6540 1850.

PASSENGER FACILITIES

LG/RF/WC.

AERODROME OBSTACLES

Unlit TWR 1,109FT AMSL PSN 370315.9S 1424719.0E. Infringes COS by 96FT.

METEOROLOGICAL INFORMATION PROVIDED

- METAR/SPECI.
- AWIS PH 03 8470 3220 - Report faults to AD OPR.
- AWIS FREQ 122.575 (requires one-second pulse to activate) - Report faults to AD OPR.

PHYSICAL CHARACTERISTICS

11/29	104	46c	PCR 60/F/D/0.65 MPa/T Centre 23 sealed.	WID 30	RWS 90
18/36	175	28a	5700 kg/0.45 MPa Sealed.	WID 18	RWS 90

AERODROME AND APPROACH LIGHTING

RWY 11/29 LIRL AFRU+PAL 119.1 SDBY PWR AVBL
RWY edge light spacing: 11/29: 58M.

OTHER LIGHTING

- Secondary PWR switchover time: 15 SEC.
- TWY LGT: Blue edge on A and B.

ATS AND AERODROME COMMUNICATION FACILITIES

FIA MELBOURNE CENTRE 125.8 On Ground

LOCAL TRAFFIC REGULATIONS

- For all ACFT, casual and short term PRKG use TWY A to the terminal.
- ACFT below 5,700KG, for longer term PRKG, tie-down area & fuel use TWY B to the APN.

FLIGHT PROCEDURES

- Right hand CCTS RQ on RWY 18 HJ and RWY 29 HN.
- Night OPS are prohibited on RWYs 18 and 36.
- RWY 18 TKOF: At RWY head turn Right to MNTN TR not less than 190DEG MAG.
- RWY 36 LDG: Base leg must be no further than 2000 FM THR.

CTAF - AFRU 119.1

ADDITIONAL INFORMATION

Kangaroo hazard exists HJ.

CHARTS RELATED TO THE AERODROME

- WAC 3469.
- Also refer AIP Departure and Approach Procedures.